



SIEGEL

Bond for Life.

Sealant Product Guide

Sealing
Bonding
Waterproofing
Weathersealing

siegeladhesives.com



GBCA
Compliant



SiegelSeal **N05+**

SiegelSeal N05+ is a high-performance neutral oxime cure silicone sealant. This premium formulation is 100% silicone and non-extended to give a lifetime performance in glazing, caulking, HVAC, roofing, guttering, stone, automotive and industrial construction applications. It is suitable for use on mirror backing, laminated glass and painted glass.

AS/NZS 4020:2018 Approved Potable Water



Download Full TDS | MSDS

Colours:		
Modulus:	Low-Medium	
Movement Capacity:	35% ±	ASTM C719
Shore A Hardness:	25	ASTM C661
Tensile Strength:	1.3 N/mm ²	ASTM D412
Elongation at Break:	≥500%	ASTM D412



SiegelSeal **N07+**

SiegelSeal N07+ is high-performance neutral oxime cure 100% silicone sealant. This formulation is engineered for a wide range of industrial applications. These include sealing lap and structural joints in applications such as automotive, HVAC, sheetmetal, roofing, guttering and waterproofing applications where lifetime high-strength sealing performance is required.

AS/NZS 4020:2018 Approved Potable Water



Download Full TDS | MSDS

Colours:		
Modulus:	Low-Medium	
Movement Capacity:	25% ±	ASTM C719
Shore A Hardness:	30	ASTM D2240
Tensile Strength:	1.5 N/mm ²	ASTM D412
Elongation at Break:	≥400%	ASTM D412



SiegelSeal **N08+**

SiegelSeal N08+ is a premium low-modulus, neutral curing silicone for lifetime performance in high movement and dynamic joint sealing applications.

This oxime curing silicone has excellent adhesion, high dynamic movement capacity and exceptional UV and weathering properties for control and expansion joints, façade caulking, perimeter sealing, hardstand and armour joints and other sealing applications.



Download Full TDS | MSDS

Colours:		
Modulus:	Low	
Movement Capacity:	-50% / +100%	ASTM C719
Shore A Hardness:	22	ASTM D2240
Tensile Strength:	1.5 N/mm ²	ASTM D412
Elongation at Break:	≥800%	ASTM D412



SiegelSeal **N09+**

SiegelSeal N09+ is a high-performance neutral alkoxy cure silicone sealant.

This MEKO free formulation is 100% silicone and non-extended to give a lifetime performance in glazing, caulking, HVAC, roofing, guttering, automotive and industrial construction applications.



Download Full TDS | MSDS

Colours:		
Modulus:	Low	
Movement Capacity:	50% ±	ASTM C920
Shore A Hardness:	25	ASTM D2240
Tensile Strength:	1.3 N/mm ²	ASTM D412
Elongation at Break:	≥250%	ASTM D412





SiegelSeal S21

SiegelSeal S21 is a premium high-performance neutral cure silicone sealant with active antifungal agents for kitchen, bathroom and wet area application.

This 100% silicone formulation is designed to give good general performance for indoor and outdoor wet area sealing with superior antifungal properties for longer service life.



Download Full TDS | MSDS

Colours:	<input checked="" type="radio"/> <input type="radio"/>	
Modulus:	Low - Medium	
Movement Capacity:	25% ±	ASTM C719
Shore A Hardness:	25	ASTM C661
Tensile Strength:	1.1 N/mm ²	ASTM D412
Elongation at Break:	≥400%	ASTM D412



SiegelFlex M20

SiegelFlex M20 is a high-performance hybrid polymer sealant and adhesive with excellent adhesion on various construction materials, providing permanent elasticity and movement capacity.

This formula is engineered to have excellent UV and weathering performance for external sealing, caulking, joint sealant and a wide range of industrial and construction applications.



Download Full TDS | MSDS

Colours:	<input checked="" type="radio"/> <input type="radio"/> <input type="radio"/>	
Modulus:	Low	
Movement Capacity:	50% ±	ASTM C719
Shore A Hardness:	30	ASTM C661
Tensile Strength:	1.1 N/mm ²	ASTM D412
Elongation at Break:	≥600%	ASTM D 412



SiegelBond M35

SiegelBond M35 is a universal adhesive and sealant for lifetime structural and elastic performance in a wide range of industrial, automotive, trade and professional applications.

This formula is engineered for extreme bond strength and dynamic flexibility for demanding bonding and sealing applications where lifetime performance is required.



Download Full TDS | MSDS

Colours:	<input checked="" type="radio"/> <input type="radio"/> <input type="radio"/>	
Modulus:	Medium - High	
Movement Capacity:	35% ±	ASTM C719
Shore A Hardness:	35	ASTM C661
Tensile Strength:	2.20 N/mm ²	ASTM D412
Elongation at Break:	600%	ASTM D412





SIEGEL

Bond for Life.



© Siegel 2025
Silicone Product Guide
Edition 1

AU 02 4868 1771
NZ 025636673
E sales@siegeladhesives.com
W siegeladhesives.com

Locations

Sydney	Melbourne	Brisbane
Adelaide	Perth	Devonport
Auckland	Mildura	Riverina