



SIEGEL

Bond for Life.

Floor Levelling Product Guide

Moisture Control
Surface Primer
Self-Levelling
Compound

siegeladhesives.com



GBCA
Compliant



SuperLevel **ECO**

SuperLevel ECO is a professional self-levelling compound, ideal for both commercial and domestic projects, can be easily applied by hand or pump. It excels at smoothing and filling uneven floors, handling thickness variations from a feather edge up to 60mm over concrete, cement, or other sound, rigid subfloors. Engineered for durability, SuperLevel ECO offers excellent resistance to loads, making it suitable for areas with wheelchair traffic, underfloor heating, and tiled surfaces

CT C25 F6



Download Full
TDS | MSDS

Key Feature Versatile self-levelling compound
Thickness 1.5 to 60 mm*
Open Time 20-30 minutes

Compression Strength	After 1 Day	After 7 Days	After 28 Days
	15.0	20.0	30.0

Flexural Strength	After 1 Day	After 7 Days	After 28 Days
	4.0	5.0	5.0



GBCA
Compliant



SuperLevel **FLEXI**

SuperLevel FLEXI is a rapid-setting, professional self-levelling compound expertly crafted for the refurbishment of both commercial and residential floors. Its versatile formulation allows for hand or pump application, effortlessly levelling, smoothing, and filling thickness variations from a feather edge up to 100mm. This robust compound adheres effectively to a wide range of interior and exterior subfloors, including concrete, cement, timber, and even rubber underlays.

CT C40 F8



Download Full
TDS | MSDS

Key Feature Flexible self-levelling compound
Thickness 1.5 to 100 mm*
Open Time 20-30 minutes

Compression Strength	After 1 Day	After 7 Days	After 28 Days
	15.0	25.0	40.0

Flexural Strength	After 1 Day	After 7 Days	After 28 Days
	5.0	7.0	8.0



GBCA
Compliant



SuperLevel **PRO**

SuperLevel PRO is a fast-setting, professional self-levelling compound designed for refurbishing existing commercial and domestic interior floors. It can be applied by hand or pump to level, smooth, and fill thickness variations from a feather edge up to 20mm per application on sound, rigid subfloors. This compound offers good resistance to loads, making it suitable for areas with wheelchair traffic, and for use with underfloor and under-tile heating systems.

CT C25 F9



Download Full
TDS | MSDS

Key Feature Smooth finish self-levelling compound
Thickness 1.5 to 20 mm*
Open Time 20-30 minutes

Compression Strength	After 1 Day	After 7 Days	After 28 Days
	15.0	22.0	28.0

Flexural Strength	After 1 Day	After 7 Days	After 28 Days
	5.0	6.0	9.0



GBCA
Compliant

*Thickness is based on a minimum of 3 mm before the installation of timber floors

SiegelProof **P12**

SiegelProof P12 is a moisture-curing polyurethane green slab primer and surface membrane which is single component, non-flammable and solvent free.

This sealer is engineered as a moisture vapor barrier for cement-based substrates including green slabs that are not subject to rising damp and have a residual humidity content up to 95% RH.

Available in 10kg drum



Download Full
TDS | MSDS

Key Feature: Single Part Rapid Cure
System: Water Based Polyurethane
Moisture Level: ■ ■ ■ ■
 <6% Moisture Reading / 95% R. H.
Coverage: 50m² (25m² / 2 Coats)
Solvent Free: Yes



GBCA
Compliant

SiegelProof **PRO2K**

SiegelProof PRO 2K is a high-performance two-component epoxy sealer and moisture barrier.

This formula provides high adhesion and long-term film strength to protect against rising damp, abrasion and both positive and negative water pressure.

Available in 10L ea. pail (Combined 20L)



Download Full
TDS | MSDS

Key Feature: Two Part High Protection
System: Water Based Epoxy
Moisture Level: ■ ■ ■ ■ ■ ■
 <30% Moisture Reading
Coverage: 100m² (50m² / 2 Coats)
Solvent Free: Yes



GBCA
Compliant

SiegelPrime **P10**

SiegelPrime P10 is a high-performance primer for porous surfaces. This one coat primer is formulated to improve adhesion and consolidate porous, dusty and powdery surfaces.

SiegelPrime P10 is fast drying, suitable for multiple substrates and forms a firm foundation for all subsequent Siegel SiegelProof and SuperLevel ranges.



Download Full
TDS | MSDS

Key Feature Ready to Use Porous Primer
System Waterbased Acrylic
Coverage 7-10m² per Litre
Suitable Substrates Concrete, masonry, render, fibre cement sheet & screeds
Solvent Free Yes



GBCA
Compliant

SiegelPrime **NP60**

SiegelPrime NP60 is a high-performance primer for non porous surfaces. This one coat primer is formulated to improve adhesion to non-porous, smooth, dense and difficult to adhere to substrates.

SiegelPrime NP60 is fast drying, suitable for multiple substrates and forms a firm foundation for all subsequent Siegel SiegelProof and SuperLevel ranges. It promotes adhesion of new coverings, toppings and adhesives without the need for surface grinding or etching.



Download Full
TDS | MSDS

Key Feature Ready to Use Non-Porous Primer
System Waterbased SBR
Coverage 15m² per Litre
Suitable Substrates Non-porous surfaces, glazed tile, most metal substrates, dense concrete & scyon boards
Solvent Free Yes



GBCA
Compliant



SIEGEL

Bond for Life.

© Siegel 2025
Floor Levelling Product Guide
Edition 1

AU 02 4868 1771
NZ 025636673
E sales@siegeladhesives.com
W siegeladhesives.com

Locations

Sydney	Melbourne	Brisbane
Adelaide	Perth	Devonport
Auckland	Mildura	Riverina

Product details and specifications are subject to change without notice. Images are for illustrative purposes only. Actual product may vary.