



Premium Fugitive Pressure Sensitive Adhesive

Product Description

Cleanspek 578 is a premium fugitive hot melt adhesive for add-ins, temporary attachment applications and printing. Formulated on a unique blend of high purity thermoplastic rubber polymers for optimal pot life. Cleanspek 578 will provide a high green bond for both manual application and high add in line speeds.

Product Advantages

- Cleanspek 578 has a medium tack strength and excellent removability.
- Cleanspek 578 is manufactured from RoHS approved raw materials.
- Cleanspek 578 maintains excellent adhesion in high temperature environments.
- Cleanspek 578 possesses high heat stability, and a low carbonisation rate.

Application

Cleanspek 770 should be applied between 130°C and 150°C through a nozzle system.

Technical Information

Adhesive type

Synthetic resins

Viscosity

175°C - 1300 cps

Ring and ball softening point

78°C

Adhesive open time

Medium - Fast

Adhesive set time

Medium

Adhesive molten tack

High

Colour

Translucent / Yellow

Shape

Pillow / Drums

Health & Safety

All the constituent parts of this adhesive comply with American FDA under CFR 21.175.105.

Health and Safety: Users must first read the Safety Data Sheet. Users should familiarize themselves with all the safety aspects of the product prior to usage.

Product Disclaimer

"Since the use and application of this product is beyond our control we cannot be held responsible for product field performance. The information presented above is the result of our considerable experience with this product but is not to be construed as a performance warranty. In every case we recommend that the customer conducts their own testing and accordingly determines, to their satisfaction, its suitability for their purpose under the operating conditions in which they will use the product/s.

For additional information, phone our Customer Service Centre on 1300 729 863.

October 2018 - This Data Sheet supersedes those previously issued.