



Premium Synthetic Glass Labelling Adhesive

Product Description

Label-lok 803 is a high wet tack, clean running gel synthetic, water-based glass labelling adhesive. It is designed to provide high adhesion onto low energy surfaces and for difficult applications. This product is designed for reliable operation on all line speeds up to 95,000 unit/ hour with no splatter, build up or labeler gumming. Label-lok 803 is made from a premium resin blend for high performance while maintaining easy clean up.

Product Advantages

- Label-lok 803 will not splatter, splash or beard at any line speed.
- Label-lok 803 is easily washed off with warm water, reducing line cleaning time.
- Label-lok 803 has excellent glass adhesion with all label types including foil.
- Label-lok 803 will provide superior performance on low surface energy glass.
- Label-lok 803 has high ice water and moisture resistance..

Application

Label-lok 803 is best applied between 26°C and 34°C at a minimal film thickness.

Technical Information

Adhesive type

Water based gel
synthetic polymers

Viscosity

20°C - 89,000 Pa.s

Colour

Off white

Ph

7.5 - 8.5

Solid Content

+/- 40%

Operating Temperature

28-34°C

Substrate Types

Glass

Health & Safety

All the constituent parts of this adhesive comply with American FDA under CFR 21.175.105.

Health and Safety: Users must first read the Safety Data Sheet. Users should familiarize themselves with all the safety aspects of the product prior to usage.

Product Disclaimer

"Since the use and application of this product is beyond our control we cannot be held responsible for product field performance. The information presented above is the result of our considerable experience with this product but is not to be construed as a performance warranty. In every case we recommend that the customer conducts their own testing and accordingly determines, to their satisfaction, its suitability for their purpose under the operating conditions in which they will use the product/s.

For additional information, phone our Customer Service Centre on 1300 729 863.

October 2018 - This Data Sheet supersedes those previously issued.