



Non-porous Surface Primer

Product Description

SiegelPrime NP60 is a high-performance primer for non-porous surfaces. This one coat primer is formulated to improve adhesion to non-porous, smooth, dense and difficult to adhere to substrates.

SiegelPrime NP60 is fast drying, suitable for multiple substrates and forms a firm foundation for all subsequent Siegel SiegelProof and SuperLevel ranges. It promotes adhesion of new coverings, toppings and adhesives without the need for surface grinding or etching.

Product Advantages

- Water resistant - suitable for use in wet areas.
- Excellent adhesion.
- Fast drying time.
- Suitable for internal and external applications.
- Easy to use.
- Tough, textured finish.

Application

Refer to the Technical Data Sheet before applying this product. Due to the wide variety of surfaces and substrates available, adhesion testing is recommended in a trial area before full application.

Suitable for priming tiles, steel, metals, dry timber and most non-porous surfaces. Also suitable for priming Siegelproof P12 and Siegelproof PRO2k

Apply 1 coat evenly as per recommended coverage rate with a roller or brush and allow to dry. Recommend coverage rate is 15m² per L - one coat required. Allow 1 hour to dry before over tilling or overcoating. Cure times will increase with reduced temperatures, high humidity or low air flow.

i Technical Information (Tested at 25°C)

Number of Coats:

1

Coverage: (per coat)

15m²/L

Wet Film: (per coat)

65 microns

Recoat

Not recommended

Overcoat:

1 hour

Colour:

Blue

Thinner/Clean Up:

Water

Shelf Life:

12 months

Surface Preparation

- Masonry should be flush pointed and all defects in existing surfaces made good.
- Surfaces must be dry, clean, sound and free from dust, grease, curing compounds, release agents, loose particles, efflorescence, concrete laitance or any other contaminants.
- Concrete must be allowed to cure for a minimum of 28 days.
- Metal surfaces must be free from rust and oxidization film. Ensure all solvent or film residue is removed.
- All high points and protrusions should be removed, blow-holes and areas of honeycombing should be filled and the surface should be brought back to an even profile using a suitable repair mortar.

Application Direction

- Refer to the Technical Data Sheet before applying this product. Due to the wide variety of surfaces and substrates available, adhesion testing is recommended in a trial area before full application.
- Apply 1 coat evenly as per recommended coverage rate with a roller or brush and allow to dry.
- Recommend coverage rate is 15m² per L – one coat required.
- Allow 1 hour to dry before over tiling or overcoating.
- Cure times will increase with reduced temperatures, high humidity or low air flow.

Application Conditions

Substrate must be dry. The use of a suitable moisture meter is recommended. Application temperature between 7°C - 35°C. Do not apply if relative humidity is above 85% during initial cure phases, or if rain is expected before cure.

Note: In humid conditions, air flow should be maximized with the use of fans to assist cure.

Limitations

- Should never be diluted
- Two or more coats not recommended
- Not suitable for proous or concrete subfloors

Health & Safety

Health and Safety: Keep out of reach of children. Contains aminosilane. May produce an allergic reaction. Safety data sheet available on request. Users must first read the Safety Data Sheet. Users should familiarize themselves with all the safety aspects of the product prior to usage.

Product Disclaimer

Since the use and application of this product is beyond our control, we cannot be held responsible for product field performance. The information presented above is the result of our considerable experience with this product but is not to be construed as a performance warranty. In every case we recommend that the customer conducts their own testing and accordingly determines, to their satisfaction, its suitability for their purpose under the operating conditions in which they will use the product/s.

For additional information, phone our Customer Service Centre on AU (02) 4858 1771 or NZ (09) 951 9552

