



## High Performance Cool Melt Adhesive

### Product Description

Ultimelt COOL 7000 is a premium high-performance cool melt packaging adhesive.

Designed as a versatile adhesive for all line speeds and substrate varieties.

### Product Advantages

- Ultimelt COOL 7000 has a long open time and a very fast set for greater line versatility.
- Ultimelt COOL 7000 has clean running, anti-charring properties reducing oxidation.
- Ultimelt COOL 7000 has superior rheological properties reducing stringing and poor cut-off.
- Ultimelt COOL 7000 possesses excellent deep freeze flexibility.

### Application

Ultimelt COOL 7000 should be applied between 120°C and 130°C through a nozzle system.

## Technical Information

**Adhesive type**

Synthetic resins

**Viscosity**

175°C - 600cps

**Ring and ball softening point**

110°C

**Adhesive open time**

Long

**Adhesive set time**

Fast

**Adhesive molten tack**

Medium

**Colour**

White

**Shape**

Granule

## Health & Safety

All the constituent parts of this adhesive comply with American FDA under CFR 21.175.105.

Health and Safety: Users must first read the Safety Data Sheet. Users should familiarize themselves with all the safety aspects of the product prior to usage.

## Product Disclaimer

"Since the use and application of this product is beyond our control we cannot be held responsible for product field performance. The information presented above is the result of our considerable experience with this product but is not to be construed as a performance warranty. In every case we recommend that the customer conducts their own testing and accordingly determines, to their satisfaction, its suitability for their purpose under the operating conditions in which they will use the product/s.

For additional information, phone our Customer Service Centre on 1300 729 863.

October 2018 - This Data Sheet supersedes those previously issued.