Bond for Life.®

Technical Data Sheet

SiegelBond M40

Surface Preparation

Glass	**Brush and remove dust**
Aluminum, light alloys, stainless steel	**Brush and remove dust**
Other metals	**Brush and remove dust**
Wood	**Brush and remove dust**
Plastics	**Brush and remove dust**
Concrete and other alkaline surfaces	**Brush and remove dust**
Mirrors	**Clean mirror back as recommended by mirror supplier.** **Ensure a primary fixing – e.g. double sided tape – is used in conjunction with the adhesive.**

Restrictions

- Must not be used in totally confined spaces where the sealant cannot cure due to lack of atmospheric moisture.
- Should not be used in conjunction with bitumen asphalt, neoprene and organic elastomers.
- Should not be painted over.
- Should not be used in application that will be submerged in chlorine water.
- Can yellow if exposed to bleach or HCL based brick cleaners while curing.
- Migration and staining can occur when used in direct contact with some natural marble and stones.

Storage and Shelf Life

- SiegelBond M40 has a shelf life of 12 months if stored unopened in the original packaging at temperatures between +5°c and +30°c.

Health & Safety

May cause an allergic skin reaction. Causes serious eye irritation. Wear protective gloves and eye protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. If skin irritation or a rash occurs: Seek medical advice/attention. If eye irritation persists: Seek medical advice/attention. Wash contaminated clothing before reuse. Keep out of reach of children. Contains aminosilane. May produce an allergic reaction. Safety data sheet available on request. For further health and safety information, check the latest safety data sheet.

Product Disclaimer

Since the use and application of this product is beyond our control, we cannot be held responsible for product field performance. The information presented above is the result of our considerable experience with this product but is not to be construed as a performance warranty. In every case we recommend that the customer conducts their own testing and accordingly determines, to their satisfaction, its suitability for their purpose under the operating conditions in which they will use the product/s.

For additional information, phone our Customer Service Centre on AU (02) 4858 1771 or NZ (09) 951 9552.
October 2024 - This Data Sheet supersedes those previously issued.